

Tandem Automatic Special Fire Extinguisher

S 9 Tandem Foam Fire Extinguisher

PG 6 Tandem Powder Fire Extinguisher

PG 12 Tandem Powder Fire Extinguisher

Description

Fights fires reliably – as well as automatically

Effective fire-fighting by hand is intuitive and easy with NEURUPPIN automatic foam and powder fire extinguishers - remove the extinguisher from its wall bracket, disarm it, press the lever, and suppress the fire. However, what happens if there is no-one there when the fire breaks out? If that happens, the NEURUPPIN tandem automatic special extinguishers are able to suppress a blaze without human intervention by automatically triggering the integrated sprinkler system. This is a safe way to suppress potential sources of fire in a limited area, such as storage facilities or boiler rooms. Even areas affected by sub-zero temperatures, e.g. outdoors, are possible - these two PG powder variants can operate down to -30°C.

Protects against potential fire loads at all times.

When these extinguishers are mounted with their standard bracket at a mounting height of 1.2 m above the floor, e.g. on a wall or a support, they are capable of automatically suppressing fires over an area of up to 3.5 m x 3.5 m (S 9 tandem) or 3.5 m x 2 m (PG 6/12 tandem). The sprinkler system is triggered whenever the temperature rises above 68°C. All three of these *Made in Germany* appliances are very rugged and long-lasting. The sprinkler sensor is protected from damage by a wire basket.

Applications

- Fire-suppression for fire classes A, B, and C
- Workshops
- Industrial premises
- Shops
- Garages
- Construction site containers
- Boiler rooms
- Warehouses
- Storage facilities for paint and refuse
- Agricultural businesses
- Domestic






E001451 / E001453 / E001455

Special advantages

- **2-in-1 for 24/7 protection** – combined handheld and automatic fire sprinklers.
- **Self-explanatory function** – for proven and safe manual operation.
- **No electrical hazards** – great safety through application tests on electrically live systems (up to 1000 V at distances of at least 1 meter)
- **Optimum jet of spray** – S 9 Tandem foam fire extinguisher with 6-fold swirl nozzles (manual operation)
- **Scannable operational capability** – standard pressure gauge displays internal pressure and protects against accidental loss of pressure, for example through previous usage, omitted maintenance or sabotage.
- **Corrosion protection included** – Steel body with high-quality, powder coating (TGCI-free) and additional 1 mm thickness of PE inner coating, double quality testing procedure.
- **Durable** – rugged design and brass pressure lever fitting
- **Wall bracket** – standard

Technical data

	S 9 Tandem	PG 6 Tandem	PG 12 Tandem
			
Fill quantity (l)	9	6	12
Extinguishing agent:	Neufoam X	Neutrex super	Neutrex super
Rating:	43A 233B C	43A 233B C	55A 233B C
Temperature (°C):	0 to 60	-30 to 60	-30 to 60
Weight (kg):	16	16	19
Width (mm):	250	230	250
Height (mm):	650	600	670
Discharge duration (s):	32* / 9**	15* / 8**	23* / 12**
Sprinkler range (m):	3.5 x 3.5**	3.5 x 2**	3.5 x 2**
Discharge width (m):	5*	6 to 7*	6 to 7*
Approvals:	CE*, EN3		

Company reserves the right to make technical modifications

* When used as a fire extinguisher (handheld)

** When used as an automatic fire extinguisher

neuruppin and other product names used in this document are brands and registered trademarks. Unauthorized use is strictly prohibited.

Made in Germany



- ✓ geschweißt
- ✓ beschichtet
- ✓ gefüllt
- ✓ geprüft

neuruppin

Höchste Qualität für Ihre Sicherheit

Your fire safety retailer: