

## Foam extinguisher (rechargeable extinguisher) S6SKeco N S9SKeco N

### Description

#### Powerful when it needs to be

In a fire involving solid or liquid substances, a ready-to-use NEURUPPIN foam extinguisher in model series S6SKeco N and S9SKeco N are ideal weapons in areas protected against sub-zero temperatures. These two powerful Made in Germany appliances with, respectively, six and nine liters of extinguishant, enable even untrained amateurs to fight fires in fire classes A or B effectively. As well as intuitive operation and a design that is easy to handle, the long discharge times and the effective extinguishant in both of these rechargeable extinguishers are sound arguments for effective fire-fighting. Targeting dispensing is possible at all times using the adjustable nozzle, e.g. for short bursts of operation.

#### Environmentally compatible, low-maintenance and versatile

Compared to conventional fire extinguishers, the extinguishant used in the S6SKeco N and S9SKeco N units has particularly good environmental credentials – This model series is certified by the German Institute of Sustainability and Economy contains a concentrate cartridge that keeps the additive for fighting B-class fires separate. This significantly reduces the cost of service.

### Examples of application

- Fire-fighting of materials in fire classes A and B (solid or liquid substances)
- Manufacturing and processing industry
- Workshop areas, trade, commerce
- Gastronomy
- Office premises
- Sales facilities
- Warehouses and logistics
- Cinemas, theaters and other performance spaces
- Administration buildings
- Medical facilities
- Educational institutions
- Domestic



### Special advantages

- **Reduction in the risk of flashback** – through a particularly tough surface coating, a great benefit when fighting fires.
- **Environmentally compatible extinguishant** – through the use of short-chain additives for fighting B-class fires.
- **Intuitive function** – also intuitive to understand for inexperienced users.
- **No impaired visibility when fighting a fire** – great advantage compared to powder extinguishers.
- **Proven and safe recharging technique** – with pushbutton and extinguisher pistol with a pressure-relief function.
- **Parkable extinguisher pistol** – good dispensing action for multiple brief bursts when fighting a fire.
- **Complies with DIN EN 3 specifications** – for use on electrical systems (up to 1000 V, 1 m minimum distance).
- **Simple and low-cost maintenance** – with big container opening, separate storage of extinguishant in concentrate cartridge as well as repeat components.
- **Long maintenance intervals** – extinguishant service life extended to six years.
- **Corrosion protection included** – Steel tank with high-quality, red powder coating (TGCI-free) and additional 1 mm thickness of PE inner coating, double quality testing procedure.
- **Made in Germany** – high quality, robust nozzle and 100% pressure testing of the tank.
- **Wall bracket** – standard in the scope of delivery.
- **Plastic base rings as standard.**

**Notice:** The German language version of this document is the official version. If this document is translated into another language, and if any difference is detected between the German version and the translation, the German version shall have precedence.

## Technical data



|                         |                                 |          |
|-------------------------|---------------------------------|----------|
| Fill quantity (L)       | 6                               | 9        |
| Extinguishing agent     | Formula A NPCA + Formula B NPCA |          |
| Rating                  | 21A 183B                        | 27A 233B |
| Fire extinguisher units | 6                               | 9        |
| Temperature (°C)        | 0 / +60                         | 0 / +60  |
| Weight (kg)             | 10.6                            | 15.6     |
| Width (mm)              | 275                             | 310      |
| Height (mm)             | 550                             | 510      |
| Discharge duration (s)  | 35                              | 66       |
| Spray width (m)         | 5                               | 5        |

Company reserves the right to make technical modifications

NEURUPPIN and other product names used in this document are brands and registered trademarks.

## Made in Germany



- ✓ geschweißt
- ✓ beschichtet
- ✓ gefüllt
- ✓ geprüft

# NEURUPPIN

Höchste Qualität für Ihre Sicherheit

Your fire safety retailer: