

## Wet Chemical Fire Extinguisher (stored pressure fire extinguisher)

**F 2 L**

**F 6 L**

**F 9 L**

### Description

#### The reliable, safe way to suppress vegetable fat and cooking oil fires

Whenever vegetable fat or cooking oil catches fire (fire class F), having an appropriate extinguishant is the A to Z of safe fire-fighting. The NEURUPPIN Series F 2 L, F 6 L and F 9 L stored pressure fire extinguisher for oil and vegetable fat fires uses Neufrol M, a reliable way of preventing explosions and flashbacks that can result from chemical reactions. These high-quality fire extinguishers are Made in Germany and are available with 2 liters, 6 liters, or 9 liters of extinguishant, so there is a suitable option for all commercial and private locations where vegetable fat and oils are heated up.

#### Discharge periods of up to 48 seconds

In emergencies, NEURUPPIN wet chemical fire extinguishers can also be operated in a simple and self-explanatory way by inexperienced users. The 9 liter model provides discharge periods of up to 48 seconds. The special swirl nozzle delivers extinguishant in an optimum manner.

### Applications

- Fire-fighting for fire classes F and A
- Restaurants
- Canteens
- Fast-food restaurants
- Hotels
- Snack bars
- Bakeries
- Laboratories
- Domestic






### Special advantages

- Great suppression power – provides safety margins
- Large discharge width – up to 5 m for high safety standards, also for inexperienced users
- Special swirl nozzle – for optimum distribution of extinguishant and droplet size
- Corresponds to EN 3-7 – suitable for the safe suppression of vegetable fat and cooking oil fires
- No electrical hazards – great safety through application tests on electrically live systems (up to 1000 V at distances of at least 1 meter)
- Safe ex-factory – 100% pressure-testing of every cylinder
- Scannable operational capability – standard pressure gage displays internal pressure of cylinder and protects against accidental loss of pressure, for example through previous usage, omitted maintenance or sabotage
- Corrosion protection included – steel body with high-quality, red powder coating (TGCI-free) and additional 1 mm thickness of PE inner coating, double quality testing procedure.
- Mobile model available – with 50 liters of extinguishant
- Valve handles made of stainless steel – available as an option
- Wall and vehicle bracket with plastic base ring – available as an option

**Notice:** The German language version of this document is the official version. If this document is translated into another language, and if any difference is detected between the German version and the translation, the German version shall have precedence.

## Technical data

|                                | F 2 L   | F 6 L  | F 9 L   |
|--------------------------------|---|--|---|
|                                |  |  |  |
| <b>Fill quantity (l)</b>       | 2   | 6  | 9   |
| <b>Extinguishing agent:</b>    | Neufrol M   |  |   |
| <b>Rating:</b>                 | 5A 40 F   | 13A 75F  | 27A 75 F  |
| <b>Temperature (°C):</b>       | 0 to +60  |  |   |
| <b>Weight (kg):</b>            | 3.9   | 11   | 14  |
| <b>Width (mm):</b>             | 140   | 225  | 240   |
| <b>Height (mm):</b>            | 390   | 560  | 540   |
| <b>Discharge duration (s):</b> | 19.5  | 33   | 48  |
| <b>Spray width (m):</b>        | 4   | 5  | 5   |

Company reserves the right to make technical modifications

NEURUPPIN and other product names used in this document are brands and registered trademarks.

## Made in Germany



- ✓ geschweißt
- ✓ beschichtet
- ✓ gefüllt
- ✓ geprüft

# NEURUPPIN

Höchste Qualität für Ihre Sicherheit

Your specialist fire protection retailer: