

Foam extinguishers (rechargeable extinguishers) S 6 Ai-TF -30/60 °C

Description

Frost-protected against Class A and B fires

For optimum fire protection in outdoor locations and in unheated interiors, the NEURUPPIN S 6 Ai-TF foam extinguisher is the ideal choice. The robust Made in Germany appliance can fight solid and liquid fires effectively. The extinguishant is frost-protected down to -30 °C making this foam extinguisher a reliable fire-fighting tool in winter.

Very high safety rating

The robust, carefully thought out and low-maintenance design of the S 6 Ai-TF typical of NEURUPPIN fire extinguishers promises long service life and high operational capability. The ergonomically optimum design and the self-explanatory functionality even enable inexperienced users to fight fires effectively: Pull out the retaining pin, press the pushbutton and direct the extinguisher nozzle at the fire. With 6 liters of extinguishant, a high rating (21 A/144 B) and an operational duration of up to 37 seconds, this appliance is able to fight fires very effectively.

Long-lasting and maintenance-friendly

With its robust, fully factory-tested steel cylinder and its corrosion-resistant fittings, the S 6 Ai-TF is a very durable appliance. In addition, the large maintenance aperture facilitates easy and time-saving service work.

Applications

- Fire-fighting for fire classes A and B
- Public facilities
- Farming & forestry
- Local public transport
- Regional & transnational passenger transport
- Goods & long-haul transport
- Manufacturing businesses & trade
- Transportation
- Warehouses & cold stores



Special advantages

- Powerful in classes A and B – fights fires very effectively indeed
- Frost-protected – operationally capable down to -30 °C
- Large discharge width – up to 6 m for high safety standards, also for inexperienced users
- Ergonomic design – convenient handle and comparatively light weight for effortless fire-fighting operations
- Easy to actuate – intuitive with a lever valve
- No electrical hazards – great safety through application tests on electrically live systems (up to 1000 V at distances of at least 1 meter)
- Safe ex-factory – 100% pressure-testing of every cylinder
- Simple to maintain – large service aperture and repeat parts
- Corrosion protection included – Steel body with high-quality, red powder coating (TGCI-free) and additional 1 mm thickness of PE inner coating, double quality testing procedure.
- Accessories available – wall and vehicle bracket with plastic base ring available as options
- Fire extinguisher registration – in acc. with DIN EN 3 and the Pressure Device Directive (CE)

Note: The German language version of this document is the official version. If this document is translated into any language other than German and there is a discrepancy between the German language version and the translation, the German language version will control.

Technical data

S 6 Ai-TF



Fill quantity (l)	6
Extinguishing agent:	Neufoam FO
Rating:	21 A / 144 B
Extinguisher units (LE)	6
Temperature (°C):	-30 / +60
Weight (kg):	12
Width (mm):	260
Height (mm):	484
Functional duration (s):	up to 37
Discharge width (m):	up to 6

Company reserves the right to make technical modifications

NEURUPPIN and other product names used in this document are brands and registered trademarks.

Made in Germany



- ✓ geschweißt
- ✓ beschichtet
- ✓ gefüllt
- ✓ geprüft

neuruppin

Höchste Qualität für Ihre Sicherheit

Your specialist fire protection retailer: