

# Water extinguisher (cartridge extinguisher) W 6 SKN W 9 SKN

## **Description**

#### The eco-friendly classics

For fire class A, pure water is a highly effective, very inexpensive and environmentally friendly extinguishing agent. The cleaning effort after extinguishing operation is also reduced – water does not cause any dirt. The NEURUPPIN water extinguishers of the W 6/9 SKN series are the classics in this segment: high-quality, durable, "Made in Germany".

#### Up to 32 seconds spraying time

The NEURUPPIN W 6 SKN and W 9 SKN charging extinguishers provide 6 litres and 9 litres of water respectively for solid fires and enable a spraying time of 23 and 32 seconds respectively. Its all-round welded steel container is reliably protected against corrosion by a 1 mm thick, doublequality-tested PE inner coating. On the outside, the container is powder-coated in high-quality red (free of TGCI).

#### Easy to use, even for inexperiences users

The propellant gas cylinder of the NEURUPPIN water charging extinguisher is located in the container and only releases its pressure during use. The extinguishers are activated in a panic-proof and self-explanatory manner by pressing the impact button. For effective and safe firefighting, the pistol grip valve can be rotated. The innovative vortex nozzle ensures optimal distribution and droplet size of the extinguishing agent.

### **Applications**

- Firefighting for fires class A
- Public institutions
- Schools
- Offices
- Administration building
- Department Stores
- Agriculture
- Transportation
- Households
- Warehouses



## **Special advantages**

- Harmless extinguishing agent water is environmentally friendly and does not require a lot of cleaning
- High extinguishing effectiveness 6 LE or 9 LE
- No visual obstruction during extinguishing due to ballistic drop jet
- Meets DIN EN3 specifications applicable against electrical systems up to 1,000 V at a safety distance of 1 m
- Tried-and-tested and safe charging technology with impact button and extinguishing gun
- Safe operation thanks to intuitively understandable functionality and extinguishing gun with integrated pressure relief function
- Large throw distance 5 m
- Safe from the factory 100 % pressure testing of each container
- Corrosion protection included proven inner and outer coating of the container
- **Easy maintenance** large service opening and repeat parts
- Low-cost refilling after use using water as an extinguishing agent
- Wall and car mount as well as plastic foot ring optionally available
- Fire extinguisher approval according to DIN EN3 and Pressure Equipment Directive (CE)

Note: The German language version of this document is the official version. If this document is translated into another language and a discrepancy between the German version and the translation is detected, the German version shall prevail.

FLN Feuerlöschgeräte Neuruppin Vertriebs-GmbH | Martin-Ebell-Strasse 4 | D-16816 Neuruppin | Germany Tel: +49 (0)3391 6890 www.fln-neuruppin.de | © 2023 Johnson Controls. All rights reserved. All specifications and other information relating to the status on the date of publication of a revised document and can be amended at any time without prior notification. | Form. No. N-2023001-00



Specifications	W 6 SKN	W 9 SKN
Capacity (I):	6	9
Extinquishing agent:	H2O	
Rating:	21A	27A
Extinguishing agent units (LE):	6	9
Temperature (°C):	+5 to +60	
Weight (kg):	10,1	14,5
Width (mm):	260	280
Height (mm):	540	510
Spraying time (s):	23	32
Spraying distance (m):	5	

NEURUPPIN and other product names mentioned in this document are trademarks and registered trademarks.



